Dell PowerEdge T150

Spec Sheet



Deliver the value of data

The Dell PowerEdge T150 affordably addresses common business workloads while delivering compute with an entry-level tower server.



Your Innovation Engine for businesses of all sizes

The Dell PowerEdge T150, powered by Intel® Xeon® E-2300 processors, delivers powerful compute for common business applications and streamlines productivity. It supports 3200 MT/s DDR4 UDIMMs, up to 128 GB for memory-intensive workloads. In addition, to address substantial throughput improvements, the PowerEdge T150 supports PCIe Gen 4 and offers enhanced thermal efficiency to support increasing power and thermal requirements. With quiet, office-friendly acoustics, the PowerEdge T150 is an ideal tower server for business critical workloads and point of sale transactions for small to midsized businesses inside and outside of the data center.

Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos to focus on growing the business. The Dell OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- · Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible, and many other tools

Protect your data assets and infrastructure with proactive resilience

The Dell PowerEdge T150 server is designed with a cyber-resilient architecture, integrating security deeply into every phase in the lifecycle, from design to retirement.

- Operate your workloads on a secure platform anchored by cryptographically trusted booting and silicon root of trust
- Maintain server firmware safety with digitally signed firmware packages
- Prevent unauthorized configuration or firmware change with system lockdown
- Securely and quickly wipe all data from storage media, including hard drives, SSDs, and system memory with System Erase
- UEFI Secure Boot prevents systems from booting from unsigned or unauthorized pre-boot device firmware, applications, and OS boot loaders, protecting systems from malware corrupting the startup process

PowerEdge T150

The Dell PowerEdge T150 offers streamlined productivity, high-speed memory and capacity, powerful compute to address common business applications. Ideal for:

- Small to mid-sized businesses
- Enhanced thermal efficiency and quiet, office-friendly acoustics for remote office/branch office
- Collaboration and sharing
- Mail, messaging and file, print

Feature	Technical Specifications		
Processor	One Intel Xeon E-2300 series processor with up to 8 cores or one Intel Pentium processor with up to 2 cores		
Memory	Four DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s		
	Supports unregistered ECC DDR4 DIMMs only		
	NOTE: For Pentium processor, maximum memory speed supported is 2666 MT/s		
Storage controllers	Internal controllers (RAID): PERC H755, PERC H355, PERC H345, HBA355i, S150		
	Internal Boot: USB, Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2 x M.2 SSDs		
	External HBAs (non-RAID): HBA355e		
Drive bays	4 x 3.5-inch cabled SAS/SATA (HDD/SSDs)		
,	Max 80 TB on 4 HDD configuration		
Power supplies	300W Bronze 100-240 VAC, cabled	300W Bronze 100-240 VAC, cabled	
	400W Platinum 100-240 VAC, cabled (available only from Dec'21)		
Fans	One cabled fan		
Dimensions	Height: 360 mm (14.17 inches)		
	• Width: 175 mm (6.88 inches)		
	Depth: 453.75 mm (17.86 inches) with bezel		
Form Factor	4U mini-tower server		
Embedded management	• iDRAC9		
	iDRAC Direct		
	iDRAC RESTful API with Redfish		
	iDRAC Service Module		
Bezel	NA		
OpenManage Software	OpenManage Enterprise		
Openivianage Contware	OpenManage Power Manager plugin		
	 OpenManage SupportAssist plugin OpenManage Update Manager plugin 		
Mobility			
Mobility	OpenManage Mobile	Ones Menera Connections	
Integrations and Connections	OpenManage Integrations	OpenManage Connections	
	BMC Truesight Misses of System Contact	IBM Tivoli Netcool/OMNIbus IBM Tivoli Network Managers IB Edition	
	Microsoft System Center Pad Llat Annible Maddelan	IBM Tivoli Network Manager IP Edition Mina Facus Operating Managers	
	Red Hat Ansible Modules National Control and a Deplication of Association of Management (Association)	Micro Focus Operations Manager	
	VMware vCenter and vRealize Operations Manager	Nagios Core	
0 "	0 1 1: 11 : 15	Nagios XI	
Security	Cryptographically signed firmware Seque Post		
	Secure Boot Secure Frage		
	Secure Erase Silican Park of Truck		
	Silicon Root of Trust System Lockdown (requires iDBACQ Enterprise or Deteceptor)		
	System Lockdown (requires iDRAC9 Enterprise or Datacenter) TDM 1 2/2 0 FIRS CC TCC continue Nation 7 TDM 2 2/2 0 FIRS CC TCC continue Nation 7 TDM 3 2/2 0 FIRS CC TCC continue Nation 7 TDM 3 2/2 0 FIRS CC TCC continue Nation 7		
Frakaddad NIIO	TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ A ChE LOM		
Embedded NIC	2 x 1 GbE LOM	D D 4	
Ports	Front Ports	Rear Ports	
	1 x iDRAC Direct (Micro-AB USB) port	• 5 x USB 2.0	
	• 1 x USB 3.0	1 x iDRAC ethernet port	
	Internal Ports	• 1 x USB 3.0	
	• 1 x USB 3.0	1 x Serial port	
DOL	4 POIs sister	• 1 x VGA	
PCle	4 PCle slots:		
	1x16 Gen4 (x16 connector) full height, half length Av4 Con4 (x3 connector) full height half length		
	1x4 Gen4 (x8 connector) full height, half length 1x4 Gen3 (x8 connector) full height helf length		
	• 1x4 Gen3 (x8 connector) full height, half length		
	1x1 Gen3 (x1 connector) full height, half length		
Operating System and Hypervisors	Canonical Ubuntu Server LTS		
	VMware ESXi		
	Microsoft Windows Server with Hyper-V		
	Red Hat Enterprise Linux		
	SUSE Linux Enterprise Server		
	For specifications and interoperability details, see Dell.com/OS		
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information,		
	visit Dell.com/OEM.		

Recommended support and services

Choose Dell ProSupport Plus or Dell ProSupport for premium hardware and software support. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit www.delltechnologies.com/Services.

APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm.

Discover more about PowerEdge servers



Learn more about our PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support