



# PowerEdge R770 CSP Edition

Open platform, cloud scale servers purpose-built for Cloud Service Providers

## Optimal Power Efficiencies and Cost-Effective Solutions

Introducing the innovative Dell PowerEdge R770 CSP Edition 2U, dual-socket cloud scale server designed to deploy high-performance computing for optimal power efficiency and cost effectiveness in large and diverse environments. Designed for high-density and scale-out workloads effectively while significantly reducing energy consumption. This reduction in energy use may also lead to lower operational costs without compromising on performance.

## Tailored to Fit Complex Datacenters

Tailored for digital and hosting service providers who offer a range of services, including max virtualization, hyperconverged and cloud-native applications, big data analytics, software-defined storage, and GPU support. The Poweredge R770 CSP Edition servers offer front I/O configurations which facilitate faster deployment and easy serviceability along with flexible system management options including Open Server Manager built on OpenBMC™.

## Cyber Resilient Architecture for Zero Trust IT environment & operations

Security is embedded throughout the entire lifecycle of PowerEdge servers, starting with a secure supply chain. A silicon-based root of trust forms the foundation for comprehensive boot security, while role-based access controls help maintain the integrity of operations. This integrated approach ensures trusted and secure server operations from deployment to decommissioning, laying a robust foundation for a Zero Trust environment.

## Increase efficiency and accelerate operations with autonomous collaboration

The Dell OpenManage™ systems management portfolio delivers a secure, efficient, and comprehensive solution for PowerEdge servers. Dell PowerEdge R770 CSP edition servers offer Dell Open Server Manager built on OpenBMC™ to provide open ecosystem systems management.

## Look to the future with Sustainability

From recycled materials in our products and packaging, to thoughtful, innovative options for energy efficiency, the PowerEdge portfolio is designed to make, deliver, and recycle products to help reduce the carbon footprint and lower your operation costs. We even make it easy to retire legacy systems responsibly with Dell Technologies Services.

## Rest easier with Dell Technologies Services

Maximize your PowerEdge Servers with comprehensive services ranging from Consulting, to ProDeploy and ProSupport suites, Data Migration and more – available across 170 locations and backed by our 60K+employees and partners.

Cloud Scale Servers offered exclusively through the Hyperscale Next program for select customers.

### PowerEdge R770 CSP Edition

The Dell PowerEdge R770 CSP Edition is powered by Intel Xeon 6 Processors, DDR5 Memory, NVMe BOSS, Energy Star compliant, advanced cooling for cloud environments. Ideal for:

- Max virtualization
- Hyperconverged and cloud-native
- Software-Defined Storage Node

Feature	Technical Specifications		
Processor	Two Intel Xeon 6 Processor with up to 144 cores per processor		
Memory	<ul style="list-style-type: none"> <li>32 DDR5 DIMM slots, supports RDIMM 2 TB max, speeds up to 6400 MT/s, Supports registered ECC DDR5 DIMMs only</li> </ul>		
Storage controllers	<ul style="list-style-type: none"> <li>Internal Boot: Boot Optimized Storage Subsystem (BOSS-N1 DC-MHS): HWRAID 1, 2 x M.2 NVMe SSDs or USB</li> </ul>		
Drive Bays	Front bays: <ul style="list-style-type: none"> <li>Up to 8 x EDSFF E3.S Gen5 NVMe (SSD) max 122.4 TB</li> <li>Up to 16 x EDSFF E3.S Gen5 NVMe (SSD) max 244.8 TB</li> </ul>		
Hot swap Power Supplies	<ul style="list-style-type: none"> <li>1500 W Titanium 100—240 VAC or 240 VDC</li> <li>1100 W Platinum 100—240 VAC or 240 VDC</li> <li>800 W Platinum 100—240 VAC or 240 VDC</li> </ul>		
Cooling Options	<ul style="list-style-type: none"> <li>Air cooling</li> </ul>		
Fans	<ul style="list-style-type: none"> <li>High performance Silver (HPR SLVR) fans/High performance Gold (HPR GOLD) fans, up to 6 hot swappable fans</li> </ul>		
Dimensions and Weight	<table border="0"> <tr> <td> <ul style="list-style-type: none"> <li>Height – 86.8 mm (3.42 inches)</li> <li>Width – 482 mm (18.97 inches)</li> <li>Weight – 28.53 kg (62.89 pound)</li> </ul> </td> <td>           Depth (for rear I/O configuration)           <ul style="list-style-type: none"> <li>802.40 mm (31.59 inches) with bezel</li> <li>801.51 mm (31.56 inches) without bezel</li> </ul>           Depth (for front I/O configuration)           <ul style="list-style-type: none"> <li>814.52 mm (32.07 inches) without bezel</li> </ul>           Note: The front I/O configuration does not support the bezel.         </td> </tr> </table>	<ul style="list-style-type: none"> <li>Height – 86.8 mm (3.42 inches)</li> <li>Width – 482 mm (18.97 inches)</li> <li>Weight – 28.53 kg (62.89 pound)</li> </ul>	Depth (for rear I/O configuration) <ul style="list-style-type: none"> <li>802.40 mm (31.59 inches) with bezel</li> <li>801.51 mm (31.56 inches) without bezel</li> </ul> Depth (for front I/O configuration) <ul style="list-style-type: none"> <li>814.52 mm (32.07 inches) without bezel</li> </ul> Note: The front I/O configuration does not support the bezel.
<ul style="list-style-type: none"> <li>Height – 86.8 mm (3.42 inches)</li> <li>Width – 482 mm (18.97 inches)</li> <li>Weight – 28.53 kg (62.89 pound)</li> </ul>	Depth (for rear I/O configuration) <ul style="list-style-type: none"> <li>802.40 mm (31.59 inches) with bezel</li> <li>801.51 mm (31.56 inches) without bezel</li> </ul> Depth (for front I/O configuration) <ul style="list-style-type: none"> <li>814.52 mm (32.07 inches) without bezel</li> </ul> Note: The front I/O configuration does not support the bezel.		
Form Factor	2U rack server		
Embedded Management	<ul style="list-style-type: none"> <li>Open Server Manager (OSM) built on OpenBMC</li> </ul>		
Security	<table border="0"> <tr> <td> <ul style="list-style-type: none"> <li>Cryptographically signed firmware</li> <li>Secure Boot</li> </ul> </td> <td> <ul style="list-style-type: none"> <li>Silicon Root of Trust</li> <li>TPM 2.0 FIPS, CC-TCG certified</li> </ul> </td> </tr> </table>	<ul style="list-style-type: none"> <li>Cryptographically signed firmware</li> <li>Secure Boot</li> </ul>	<ul style="list-style-type: none"> <li>Silicon Root of Trust</li> <li>TPM 2.0 FIPS, CC-TCG certified</li> </ul>
<ul style="list-style-type: none"> <li>Cryptographically signed firmware</li> <li>Secure Boot</li> </ul>	<ul style="list-style-type: none"> <li>Silicon Root of Trust</li> <li>TPM 2.0 FIPS, CC-TCG certified</li> </ul>		
Network options	OCP NIC card 3.0 : 2 slots on the front or 2 slots on the rear		
GPU options	Up to 4 x 75 W SW		
Ports	<table border="0"> <tr> <td>           Front Ports:           <ul style="list-style-type: none"> <li>1 x USB 2.0 Type C port</li> <li>1 x USB 2.0 Type A port (optional)</li> <li>1 x Mini-DisplayPort (optional)</li> <li>1 x DB9 Serial (with front I/O configuration)</li> <li>1 x Dedicated BMC Ethernet port (with front I/O configuration)</li> </ul>           Internal Ports:           <ul style="list-style-type: none"> <li>1 x USB 3.1 Type A port (optional)</li> </ul> </td> <td>           Rear Ports:           <ul style="list-style-type: none"> <li>1 x Dedicated BMC Ethernet port</li> <li>1 x VGA</li> <li>2 x USB 3.1 Type A ports</li> </ul> </td> </tr> </table>	Front Ports: <ul style="list-style-type: none"> <li>1 x USB 2.0 Type C port</li> <li>1 x USB 2.0 Type A port (optional)</li> <li>1 x Mini-DisplayPort (optional)</li> <li>1 x DB9 Serial (with front I/O configuration)</li> <li>1 x Dedicated BMC Ethernet port (with front I/O configuration)</li> </ul> Internal Ports: <ul style="list-style-type: none"> <li>1 x USB 3.1 Type A port (optional)</li> </ul>	Rear Ports: <ul style="list-style-type: none"> <li>1 x Dedicated BMC Ethernet port</li> <li>1 x VGA</li> <li>2 x USB 3.1 Type A ports</li> </ul>
Front Ports: <ul style="list-style-type: none"> <li>1 x USB 2.0 Type C port</li> <li>1 x USB 2.0 Type A port (optional)</li> <li>1 x Mini-DisplayPort (optional)</li> <li>1 x DB9 Serial (with front I/O configuration)</li> <li>1 x Dedicated BMC Ethernet port (with front I/O configuration)</li> </ul> Internal Ports: <ul style="list-style-type: none"> <li>1 x USB 3.1 Type A port (optional)</li> </ul>	Rear Ports: <ul style="list-style-type: none"> <li>1 x Dedicated BMC Ethernet port</li> <li>1 x VGA</li> <li>2 x USB 3.1 Type A ports</li> </ul>		
PCIe	<ul style="list-style-type: none"> <li>Up to 4 x16 Gen5 PCIe slots</li> </ul>		
Operating System and Hypervisors	<ul style="list-style-type: none"> <li>Canonical Ubuntu Server LTS</li> <li>Red Hat Enterprise Linux</li> <li>SUSE Linux Enterprise Server</li> </ul> For specifications and interoperability details, see <a href="https://www.dell.com/osupport">Dell.com/OSsupport</a> .		
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit <a href="https://www.dell.com">Dell.com</a> -> Solutions -> OEM Solutions.		

## APEX Flex on Demand

Acquire the technology you need to support your changing business with payments that scale to match actual usage. For more information, visit <https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm>.

Discover more about PowerEdge servers



Learn more about services for PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on X (formerly Twitter)



Contact a Dell Technologies Expert for Sales or Support