

## Deliver the value of data

The Dell EMC OEM PowerEdge R250 affordably addresses common business applications—while delivering compute within entry-level 1U rack server.



## Your Innovation Engine for businesses of all sizes

The Dell EMC OEM PowerEdge R250, powered by Intel® Xeon® E-2300 processors, delivers powerful compute for common business applications and streamlines productivity. It supports 3200 MT/s DDR4 speeds and 32 GB DIMMs, up to 128 GB for memory intensive workloads. In addition, to address substantial throughput improvements, the PowerEdge R250 supports PCIe Gen 4 and offers enhanced thermal efficiency to support increasing power and thermal requirements. This makes the PowerEdge R250 an ideal server for collaboration and sharing and a variety of workloads including mail and messaging, file and print, web hosting, and point of sale environments in a 1U form factor for small to mid-sized businesses and remote offices and branch offices.

## Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools

## Protect your data assets and infrastructure with proactive resilience

The Dell EMC OEM PowerEdge R250 server is designed with a cyber-resilient architecture, integrating security deeply into every phase in the lifecycle, from design to retirement.

- Operate your workloads on a secure platform anchored by cryptographically trusted booting and silicon root of trust
- Maintain server firmware safety with digitally signed firmware packages
- Prevent unauthorized configuration or firmware change with system lockdown
- Securely and quickly wipe all data from storage media, including hard drives, SSDs and system memory with System Erase

### OEM PowerEdge R250

The Dell EMC OEM PowerEdge R250 offers streamlined productivity, high-speed memory and capacity, powerful compute to address common business applications.

Ideal for:

- Small mid-sized businesses
- Remote office/branch office
- Collaboration and sharing
- Mail/messaging and file/print

Feature	Technical Specifications	
Processor	One Intel Xeon E-2300 series processor with up to 8 cores or one Intel Pentium processor with up to 2 cores	
Memory	4 DDR4 DIMM slots, supports UDIMM 128 GB max, speeds up to 3200 MT/s Note: For Pentium processor, the maximum memory speed is 2666 MT/s.	
Storage controllers	<ul style="list-style-type: none"> <li>Internal controllers: PERC H345, H755, HBA355i, S150</li> <li>Boot optimized Storage Subsystem</li> <li>External HBAs (RAID): HBA355e</li> <li>External HBAs (non-RAID): 12 Gbps SAS HBA</li> </ul>	
Drive bays	<ul style="list-style-type: none"> <li>Up to 4 x 3.5-inch hot swap SAS/SATA (HDD/SSD) max 30.72 TB</li> <li>Up to 2 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 15.36 TB</li> <li>Up to 4 x 3.5-inch cabled SAS/SATA (HDD/SSD) max 30.72 TB</li> </ul>	
Power supplies	<ul style="list-style-type: none"> <li>450 W Bronze AC/240 V cabled power supply</li> <li>450 W Platinum AC/240 V cabled power supply</li> </ul>	
Cooling options	Air cooling	
Fans	<ul style="list-style-type: none"> <li>Up to four cabled fans</li> </ul>	
Dimension	<ul style="list-style-type: none"> <li>Height: 42.8 mm (1.68 inches)</li> <li>Width: 482.6 mm (19 inches)</li> <li>Depth: 598.64 mm (23.56 inches) with bezel 585 mm (23.03 inches) without bezel</li> </ul>	
Form Factor	1U rack server	
Embedded management	<ul style="list-style-type: none"> <li>iDRAC9</li> <li>iDRAC Direct</li> <li>iDRAC RESTful with Redfish</li> <li>iDRAC Service Manual</li> </ul>	
Bezel	Optional bezel or security bezel	
OpenManage Software	<ul style="list-style-type: none"> <li>OpenManage Enterprise</li> <li>OpenManage Power Manager plugin</li> <li>OpenManage SupportAssist plugin</li> <li>OpenManage Update Manager plugin</li> </ul>	
Mobility	OpenManage Mobile	
Integrations and Connections	OpenManage Integrations	OpenManage Connections
	<ul style="list-style-type: none"> <li>BMC Truesight</li> <li>Microsoft System Center</li> <li>Red Hat Ansible Modules</li> <li>VMware vCenter and vRealize Operations Manager</li> </ul>	<ul style="list-style-type: none"> <li>IBM Tivoli Netcool/OMNibus</li> <li>IBM Tivoli Network Manager IP Edition</li> <li>Micro Focus Operations Manager</li> <li>Nagios Core</li> <li>Nagios XI</li> </ul>
Security	<ul style="list-style-type: none"> <li>Cryptographically signed firmware</li> <li>Secure Boot</li> <li>Secure Erase</li> <li>Silicon Root of Trust</li> <li>System Lockdown (requires iDRAC9 Enterprise or Datacenter)</li> <li>TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ</li> </ul>	
Embedded NIC	2 x 1 GbE LOM	
GPU options	Not supported	
Ports	Front Ports	Rear Ports
	<ul style="list-style-type: none"> <li>1 x USB 2.0</li> <li>1 x iDRAC Direct (Micro-AB USB) port</li> </ul>	<ul style="list-style-type: none"> <li>1 x USB 2.0</li> <li>1 x USB 3.0</li> <li>1 x VGA</li> <li>1 x Serial port</li> </ul>
		Internal Ports
		<ul style="list-style-type: none"> <li>1 x USB 3.0 (optional)</li> </ul>
PCIe	2 x PCIe Gen4 slots	
Operating System and Hypervisors	<ul style="list-style-type: none"> <li>Canonical Ubuntu Server LTS</li> <li>Citrix Hypervisor</li> <li>Microsoft Windows Server with Hyper-V</li> <li>Red Hat Enterprise Linux</li> <li>SUSE Linux Enterprise Server</li> <li>VMware ESXi*</li> </ul> <p>*support only from Dec'21</p> <p>For specifications and interoperability details, see <a href="https://www.dell.com/ossupport">Dell.com/OSsupport</a>.</p>	
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit <a href="https://www.dell.com/oem">Dell.com/OEM</a> .	
OEM-XE version available	OEM Products that feature up to a 9 month longer life cycle than standard products. For more information visit <a href="https://www.dell.com/oem">Dell.com/OEM</a>	

## Recommended support and services

Dell ProSupport Plus for critical systems or Dell ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit [Dell.com/ServiceDescriptions](https://www.dell.com/ServiceDescriptions).

## APEX Flex on Demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit [www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm](https://www.delltechnologies.com/en-us/payment-solutions/flexible-consumption/flex-on-demand.htm).

### Discover more about PowerEdge servers



Learn more about our PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for [Sales](#) or [Support](#)